

# NIFTY® BASIC

(F18BASIC) 444 mm x 450 M 4 rls/cs  
Approximate metric equivalent for 18" x 1500'

The traditional method of stretching film around the pallet is time consuming and takes a lot of operator energy. **New hybrid films, like the F18BASIC light gauge performance film, are stiffer films that are easier to apply and have less neck down than standard films.** Also, being able to apply the film by walking naturally forward around the pallet is **easier, safer, and less time consuming** than the old "backwards" method. Traditional 80 gauge films need to be stretched 100% for maximum effectiveness – most operators only stretch it about 30% in application. This leaves too much stretch in the film which allows the load to shift during transit. F18BASIC hybrid film is already pre-stretched so **the hold is tighter** cutting down substantially on shifting in transport. It is also a **much lighter weight roll** making application **more efficient** and reducing/virtually eliminating operator fatigue.

- **Less film used = less cost**
- **Lighter weight roll = less operator fatigue**
- **Pre-stretch = load stabilization**
- **No neckdown = more coverage on each pass**
- **Raised core = less damage to edge of roll = less waste**



NIFTY Products. 4 Jocama Blvd, Old Bridge, NJ 08857  
800-631-2172 732-591-1140 FAX: 732-591-8477  
[www.niftypack.com](http://www.niftypack.com)